

Twin-Shaft Continuous Mixer (LFK)

Technical data

PERFORMANCE DATA

Type	Mixing circle diameter	Mixing distance	Mixing throughput ¹⁾			Feed size (max.)	Drive power
			Lean concrete/RCC	Mineral mixes	Fines (dry) ²⁾		
LFK 0526	530 mm	2,600 mm	50 - 20 t/h	50 - 130 t/h	30 - 90 t/h	32 mm	18.5 kW
LFK 0626	630 mm	2,600 mm	100 - 220 t/h	100 - 230 t/h	50 - 130 t/h	45 mm	22 kW
LFK 0726	750 mm	2,600 mm	150 - 325 t/h	150 - 350 t/h	70 - 220 t/h	64 mm	37 kW
LFK 0926	900 mm	2,600 mm	200 - 550 t/h	200 - 700 t/h	110 - 330 t/h	64 mm	55 kW
LFK 1130	1,100 mm	3,000 mm	350 - 850 t/h	350 - 1,200 t/h	190 - 550 t/h	80 mm	2 x 37 kW

DIMENSIONS AND WEIGHTS

Type	A	B	C	D	E	Weight ³⁾
LFK 0526	3,520 mm	1,070 mm	1,190 mm	1,100 mm	1,100 mm	2,600 kg
LFK 0626	3,530 mm	1,250 mm	1,330 mm	1,200 mm	1,330 mm	3,100 kg
LFK 0726	3,650 mm	1,440 mm	1,480 mm	1,200 mm	1,500 mm	5,100 kg
LFK 0926	3,950 mm	2,000 mm	1,860 mm	1,385 mm	1,850 mm	6,100 kg
LFK 1130	4,250 mm	2,370 mm	2,050 mm	1,600 mm	2,260 mm	9,900 kg

¹⁾ Throughput capacity for other aggregates available on request.

²⁾ Material density 1.00 t/m³.

³⁾ Weight for standard model without accessories.

All technical data shown here refer to the standard version.

The technical data for customer-specific versions may vary from the information shown here.

All technical data may change due to development.

Subject to modification without notice.

